


BAZ-2

Technical Data Sheet



Type	Multi-inductor hardening machine
Number of hardening stations	1 or 2 based on required cycle time
Number of inductors	2-13 based on cycle time
No. of inductors for end sections	2
Positioning of inductors	NC drive/pneumatic
Travel speed of inductors	Max. 150 mm/s
Positioning of inductors (pitch adjustment of inductors)	Manual or NC drive
Lowering/raising of inductors	NC drive
Adjustment of spindle units	Manual or NC drive
Rotary drive of component	NC drive
Rotation speed	0-100 rpm
Length compensation	Spring system
Standard MF output	3 × 80 kW
Control system	Siemens Sinumerik ONE Siemens S7-15xx PLC
NC servo technology	Siemens Sinamics S120/CU320
HMI	Siemens IPC427E/OP15-Black Siemens IPC477E
Manual controller	Siemens MPP483/MCP483/KP8
Process monitoring	Inverter central supply unit with monitoring in PLC or EME2020
Monitoring of quenching medium	Volume control with pump drive Flow monitoring with PLC or EME2020
Safety technology	Pilz safety relay or Siemens – Safety Integrated ET200SP/Profisafe
Spray protection enclosure	Encapsulated
Steam extraction	Integrated, centralised or decentralised, optionally with air filter
Condensate recovery	Integrated
Dimensions (L × W × H)	7,400 × 2,500 × 2,500 mm (1 stat.) 7,400 × 5,200 × 2,500 mm (2 stat.)
Total height	2,300/3,000 mm
Total weight	Approx. 14 t

Options

- › Tempering via residual heat
- › Process monitoring and data capture (EME)
- › Connection to automatic part handling systems
- › Washing machine with control via HM: separate
- › Water-to-water or water-to-air chiller
- › Total indicated runout (TIR): integrated
- › Inductor recognition
- › Inductor database
- › Interfaces for data transfer
- › Hardening units for end sections
- › Automatic pitch setting of inductors
- › Detection system (e.g. for DMC)
- › Marking system (e.g. needle embosser)
- › Monitoring of quenching water quantity via EME
- › Maintenance reminder in machine control system
- › Monitoring of hardening result (lab equipment)

Component handling

Loading	From above
Unloading	From above
Loading height	1,100 mm
Loading/unloading	Gantry loader, opt. manual
Manual loading (option)	Via safety door
Manual unloading (option)	Via safety door

Applications

Crankshafts	All types
Max. length	700 mm
Max. swing diameter	200 mm
Max. weight	30 kg
No. of pin bearings	Variable
No. of main bearings	Variable
Cycle time	35 s
Machining orientation	Horizontal
Clamping technique	Three-jaw chuck/tailstock centre
Inductor design, main/pin bearing	Half shell inductor
Inductor design, end sections	Half shell or ring inductor