

SELF CENTRIC VISE — SCV 80 / 125 / 225

Scope of Application

- Ideal for use on 3, 4 & 5 Axis Machining centers due to its compact design
- Horizontal Installation-Suitable for **Vertical Machining Centers**
- Vertical Installation Suitable for **Horizontal Machining Centers**

Product Features


- · Heavy duty high precise self-centric clamping vise with good repeatability
- · Compact design with best accessibility
- Interface for ZPS clamping and mounting holes as standard
- Spindle screw Blackodising (for high hardness, wear, corrosion resistance and excellent lubricity)
- 4 Bolt jaw mounting for Increased Clamping Force
- Provision of M5 holes for mounting additional Jaws
- Serrated gripper teeth for superior bite with 45° Dovetail provision
- Featuring a dowel pin for better accuracy in Jaws
- High material savings due to minimal clamping edge requirements
- 3mm gripp clamping is possible

Gripp Clamping


- · With the clamping jaw systems you can clamp parallel workpieces safely and quickly.
- Stamping and clamping takes place in one work step.







Technical Data



| Variant | | SCV 80 | SCV 125 | SCV 225 |
|---------------------|----|---------|---------|---------|
| Dimensions in mm | а | 105 | 150 | 250 |
| | b | 80 | 125 | 125 |
| | е | 60 | 100 | 96 |
| | f | 52±0.01 | 52±0.01 | 96±0.02 |
| | g | N/A | N/A | 100 |
| | h | N/A | N/A | 200 |
| | р | 35.8 | 50 | 50 |
| | q | 7.5 | 7.5 | 7.5 |
| | r | 49 | 68 | 68 |
| | S | 116 | 167 | 267 |
| | t | 57 | 82 | 82 |
| | Х | 54 | 79 | 79 |
| | У | 123 | 166 | 266 |
| | C1 | 74 | 120 | 220 |
| | C2 | 80 | 125 | 225 |
| | СЗ | 36 | 68 | 168 |
| | C4 | 42 | 73 | 173 |

| Variant | SCV 80-80 | SCV 125-125 | SCV 125-225 |
|--|------------------|-------------------|-------------------|
| Dimensions (mm) | 105 x 80 x 57 | 150 X 125 X 82 | 150 X 225 X 82 |
| Clamping Range (Forword Jaws) (mm) | 6 - 40.3 | 6-73 | 6-173 |
| Clamping Range (Reversed Jaws) (mm) | 38.5 – 76.3 | 55-125 | 55-225 |
| Maximum Clamping Fource (kN) | 22 | 20 | 20 |
| Maximum Torque Force (Nm) | 60 | 100 | 100 |
| Weight (Kg) | 2.5 | 8 | 11 |

Scope Of Supply

- Self Centric Vise with Clamping Jaws 1 No
- Work Piece Stopper -1 No.
- Side Clamp 4 Nos
- Rachet With Socket 1 No

SELF CENTRIC VISE - ACCESSORIES

Soft Jaws

- For holding parts that would be difficult to fixture with standard, flat vise jaws during machining.
- Suitable for Profile and Irregular shape workpiece.



* On Request

For clamping two work pieces simultaneously Installation between both the jaws * On Request

Riser Block/Console

For raising the Self Centric SCV 125/225
 Improved access for five-sided machining



* On Request

Zero Point System

 For Quick clamping and alignment of Vise Allows you to clamp parts with accuracy, speed, ease and flexibility using retractable nipples and fast-closing clamps



* On Request

Adaptor Plate

Adaptor plate for 4th and
 5th axis Rotating axis – Diameter
 160 mm and 200 mm



* On Request

Pyramid

 The pyramid work holding bundles facilitate clamping of three individual components in one fixture and completed in a single setup.



* On Request